



# Aluminium Scaffold Towers Ltd.

01353 778811



sales@aluminium-scaffoldtowers.co.uk

www.aluminium-scaffoldtowers.co.uk

## 1450 Mobile Aluminium Scaffold Tower Tested and Certified to EN 1004-1:2020



Type Approved  
Safety  
Regular Production  
Surveillance  
www.tuv.com  
ID: 1111247258

Tower Dimension : 1.45m(W) x 1.8m(L) x 4.2m(H)  
Max. Platform Height : 3.2m, Max. Working Height : 5.2m

Maximum Working Load :  
Tower - 950 kg including tower self weight  
Platform - 275 kg when load uniformly distributed

| Item | Description                          | Qty. |
|------|--------------------------------------|------|
| 1.   | Castor Wheel 150mm dia. W/Adj. Leg   | 4    |
| 2.   | 1450 2 Rung Ladder Frame 1.45 x 1.0m | -    |
| 3.   | 1450 2 Rung Span Frame 1.45 x 1.0m   | -    |
| 4.   | 1450 3 Rung Ladder Frame 1.45 x 1.5m | -    |
| 5.   | 1450 3 Rung Span Frame 1.45 x 1.5m   | -    |
| 6.   | 1450 4 Rung Ladder Frame 1.45 x 2.0m | 2    |
| 7.   | 1450 4 Rung Span Frame 1.45 x 2.0m   | 2    |
| 8.   | Trapdoor Platform 600 x 1800         | 2    |
| 9.   | Fixed Platform 600 x 1800            | 1    |
| 10.  | Horizontal Brace 1800 (Red)          | 10   |
| 11.  | Diagonal Brace 2100 (Blue)           | 5    |
| 12.  | Folding Toeboard 1200 x 1800         | 1    |
| 13.  | Fixed Outrigger - Small              | 4    |
| 14.  | Telescopic Outrigger - Medium        | -    |
| 15.  | Telescopic Outrigger - Large         | -    |

Scale : NTS

Ref. : DW-4200-18

Weight : approx. 144.0 kg

