



Aluminium Scaffold Towers Ltd.

01353 778811

sales@aluminium-scaffoldtowers.co.uk

www.aluminium-scaffoldtowers.co.uk

1450 Mobile Aluminium Scaffold Tower Tested and Certified to EN 1004-1:2020



Type Approved
Safety
Regular Production
Surveillance
www.tuv.com
ID: 1111247258

Tower Dimension : 1.45m(W) x 2.5m(L) x 4.2m(H)
Max. Platform Height : 3.2m, Max. Working Height : 5.2m

Maximum Working Load :
Tower - 950 kg including tower self weight
Platform - 275 kg when load uniformly distributed

Item	Description	Qty.
1.	Castor Wheel 150mm dia. W/Adj. Leg	4
2.	1450 2 Rung Ladder Frame 1.45 x 1.0m	-
3.	1450 2 Rung Span Frame 1.45 x 1.0m	-
4.	1450 3 Rung Ladder Frame 1.45 x 1.5m	-
5.	1450 3 Rung Span Frame 1.45 x 1.5m	-
6.	1450 4 Rung Ladder Frame 1.45 x 2.0m	2
7.	1450 4 Rung Span Frame 1.45 x 2.0m	2
8.	Trapdoor Platform 600 x 2500	2
9.	Fixed Platform 600 x 2500	1
10.	Horizontal Brace 2500 (Red)	10
11.	Diagonal Brace 2700 (Blue)	5
12.	Folding Toeboard 1200 x 2500	1
13.	Fixed Outrigger - Small	4
14.	Telescopic Outrigger - Medium	-
15.	Telescopic Outrigger - Large	-

Scale : NTS

Ref. : DW-4200-25

Weight : approx. 164.0 kg

