



# Aluminium Scaffold Towers Ltd.

01353 778811

sales@aluminium-scaffoldtowers.co.uk

www.aluminium-scaffoldtowers.co.uk

## 1450 Mobile Aluminium Scaffold Tower Tested and Certified to EN 1004-1:2020



Type Approved  
Safety  
Regular Production  
Surveillance  
www.tuv.com  
ID: 1111247258

Tower Dimension : 1.45m(W) x 2.5m(L) x 6.2m(H)  
Max. Platform Height : 5.2m, Max. Working Height : 7.2m

Maximum Working Load :  
Tower - 950 kg including tower self weight  
Platform - 275 kg when load uniformly distributed

| Item | Description                          | Qty. |
|------|--------------------------------------|------|
| 1.   | Castor Wheel 150mm dia. W/Adj. Leg   | 4    |
| 2.   | 1450 2 Rung Ladder Frame 1.45 x 1.0m | -    |
| 3.   | 1450 2 Rung Span Frame 1.45 x 1.0m   | -    |
| 4.   | 1450 3 Rung Ladder Frame 1.45 x 1.5m | -    |
| 5.   | 1450 3 Rung Span Frame 1.45 x 1.5m   | -    |
| 6.   | 1450 4 Rung Ladder Frame 1.45 x 2.0m | 3    |
| 7.   | 1450 4 Rung Span Frame 1.45 x 2.0m   | 3    |
| 8.   | Trapdoor Platform 600 x 2500         | 3    |
| 9.   | Fixed Platform 600 x 2500            | 1    |
| 10.  | Horizontal Brace 2500 (Red)          | 14   |
| 11.  | Diagonal Brace 2700 (Blue)           | 9    |
| 12.  | Folding Toeboard 1200 x 2500         | 1    |
| 13.  | Fixed Outrigger - Small              | -    |
| 14.  | Telescopic Outrigger - Medium        | 4    |
| 15.  | Telescopic Outrigger - Large         | -    |

Scale : NTS

Ref. : DW-6200-25

Weight : approx. 223.2 kg

