



Aluminium Scaffold Towers Ltd.

01353 778811

sales@aluminium-scaffoldtowers.co.uk

www.aluminium-scaffoldtowers.co.uk

1450 Mobile Aluminium Scaffold Tower Tested and Certified to EN 1004-1:2020



Type Approved
Safety
Regular Production
Surveillance
www.tuv.com
ID: 1111247258

Tower Dimension : 1.45m(W) x 2.5m(L) x 8.7m(H)
Max. Platform Height : 7.7m, Max. Working Height : 9.7m

Maximum Working Load :
Tower - 950 kg including tower self weight
Platform - 275 kg when load uniformly distributed

Item	Description	Qty.
1.	Castor Wheel 150mm dia. W/Adj. Leg	4
2.	1450 2 Rung Ladder Frame 1.45 x 1.0m	1
3.	1450 2 Rung Span Frame 1.45 x 1.0m	1
4.	1450 3 Rung Ladder Frame 1.45 x 1.5m	1
5.	1450 3 Rung Span Frame 1.45 x 1.5m	1
6.	1450 4 Rung Ladder Frame 1.45 x 2.0m	3
7.	1450 4 Rung Span Frame 1.45 x 2.0m	3
8.	Trapdoor Platform 600 x 2500	4
9.	Fixed Platform 600 x 2500	1
10.	Horizontal Brace 2500 (Red)	18
11.	Diagonal Brace 2700 (Blue)	14
12.	Folding Toeboard 1200 x 2500	1
13.	Fixed Outrigger - Small	-
14.	Telescopic Outrigger - Medium	4
15.	Telescopic Outrigger - Large	-

Scale : NTS

Ref. : DW-8700-25

Weight : approx. 294.3 kg

